



Technical features

Charging capacity per connector	3.7 kW, 7.4 kW, 11 kW, 22 kW
Charge mode	Mode 3, Z.E. Ready
Connector type	Type 2
Number of connectors	1 or 2
CE certified	Yes
Output power	1-phase or 3-phase, 230V – 400V, 16A and 32A
Temperature range	-25°C to +60°C
Moisture (non-regulating)	Max. 95%
Authorization	Auto START / Keyfob / RFID card
Information status	LED ring
Communication	GPS / GSM / UMTS / GPRS Modem / controller with RFID reader
Communication protocol	OCPP 1.2, 1.5 and 1.6

Physical features

Designed according to	IEC 61851-1 (2010), EC 61851-22 (2002)
Protection	IP54, IK10
Installation instructions	EN/IEC 61000-32 (2014), EN/IEC 61000-3-3 (2013) EN/IEC 61000-6-2 (2016), EN/IEC 61000-6-3 (2007) + A1 (2011) EN/IEC 60335-1 (2012) +A13 (2017), EN/IEC 60364-4-41 (2017) EN/IEC 60529-1 (1989) +A1 (1999) + A2 (2013) EN/IEC 60950-1 (2005) + A1 (2009) + A2 (2013) EN/IEC 60950-22 (2017), EN/IEC 61851-1 (2017) EN/IEC 61851-22 (2002), EN/IEC 62196-1 (2014) EN/IEC 62196-2 (2017)

Housing	Polycarbonate
Dimensions (mm)	600 x 255 x 410 mm (double socket) 600 x 255 x 205 mm (single socket)
Weight	11 kg (max.)
Mounting	Wall or pole
Standard colors	RAL 5017 (blue), RAL 7016 (dark grey), RAL 7042 (light grey), RAL 9016 (white)

All online charging stations include a MID-certified kWh meter.

Copyright © 2019 EVBox Manufacturing B.V. EVBox® and the EVBox logo are registered trademarks. All rights reserved. EVBox has compiled this document to the best of its knowledge but does not warrant that all information provided is error-free; EVBox does not accept liability in that respect. All specifications are approximates only. The limited warranty conditions are stated in the applicable EVBox general terms and conditions. EVBP1_BL_EN_072019 © EVBox Manufacturing B.V.

EVBox Manufacturing B.V.
Fred. Roeskestraat 115
1076 EE Amsterdam
The Netherlands
evbox.com/support